

Lift Nubbin For Flush Joint Casing

The UMS Flowell Lift Nubbin for flush joint casing allows handling of flush joint casing and tubing. The Flush Joint Casing Clamp Nubbins have a pin thread to mate with the corresponding flush joint box thread on the casing or tubing.

A 4.75 ton swivel allows single joints to be lifted with the tugger line or crane without the need for single joint elevators. A shoulder on the lift nubbin acts as a dummy coupling and allows the string to be handled with side door or centre latch elevators.

If slip type elevators are used, the dummy coupling shoulder acts as a stop collar in the event that unplanned string slippage occurs.

FEATURES & BENEFITS

- Lightweight
- Available in tubing and casing sizes from 2-1/8" upwards
- Various thread options
- Swivel hoist to allow make up of tubing / casing
- Elevator shoulder for picking up string weight or used as a stop shoulder when using slip type elevators

SPECIFICATIONS

- 4.75 Ton SWL swivel hoist ring
- Elevator shoulder rating dependent on thread size, thread type, grade, and tubing/ casing weight



Technical Specifications - Lift Nubbin For Flush Joint Casing

Part Number	Thread Connection	WLL (Te)
LN-7625-297-FJL	7-5/8" 29.7# VAM FJL PIN	50
LN-7625-337-FJL	7-5/8" 33.7# VAM FJL PIN	50
SLN-7625-337-TSH513	7-5/8" 33.7# TENARIS WEDGE 513 PIN	50
SLN-8625-01-STL	8-5/8" 40# ATLAS BRADFORD ST-L PIN	50
SLN862502TW513	8-5/8" 40# TENARIS WEDGE 513 PIN	50

