Non-Sealing Pod Worktable

The worktable for the non-sealing pod is a lightweight worktable that is an elevated C-plate arrangement allowing the MLE and service lines to enter the shroud without the risk of damage when landing the ESP lifting clamp.

The C-shape opening is large enough to fit past the outside of the ESP so that it can be installed or removed at anytime from the top of the shroud sleeve.

UMS Flowell
Performance Under Pressure

Non-Sealing Pod Worktable

Features & Benefits

- Lightweight design with lifting handles
- C-shape to allow assembly and removal with the ESP installed
- Elevated level so that MLE and service lines can enter the shroud without the risk of damage

Specifications

- 10Te SWL

©UMS Flowell 2025

UMS Flowell
Performance Under Pressure

Non-Sealing Pod Worktable

Part Number	Shroud size (in)
WT-0043	7 or 7-5/8

UMS Flowell - Turriff, South Bogton, Forglen, Turriff, Aberdeenshire, Scotland, UK, AB53 4LA. Tel: +44 (0)1888 568771

UMS Flowell - East Kilbride, Suite 10, Arx house, James Watt Avenue,
Scottish Enterprise Technology Park, East Kilbride, Scotland, UK, G75 0QD Tel: +44 (0)1355 222611

©UMS Flowell 2025